



Cyclone Air Shaker & Pedestal

- Q. Is the shaker approved for hazardous areas?
A. Yes, the Cyclone shaker will work in all areas.
- Q. What is the speed or RPM of the shaker?
A. The shaker operates at 100 rpm to 700 RPM.
- Q. What is the warranty covering the shaker parts and labor?
A. There is a three year limited warranty for parts and labor on the Cyclone Shaker.
- Q. How long should I shake the paint?
A. Refer to your paint manufacturers recommendation.
- Q. What size cans can be shaken on the Cyclone Shaker?
A. The Shaker accommodates Pints, Gallons, Imperial Gallons, Aerosols, Rectangular Gallons, Half Liter, One Liter, Four Liter, and some Five liter cans.
- Q. Can the speed of the shaker be adjusted to slow it down or speed it up?
A. Yes, the Cyclone Air shaker speed is adjustable.
- Q. What is the maximum weight recommended for the shaker during operation?
A. Approximately sixteen pounds.
- Q. How tight should the U-bolts on the can clamp be tightened?
A. The U-bolt nuts should be tightened to 28 ft. lbs (388 kg. cm.) of torque.
- Q. Does the shaker require a pedestal to mount it to or can I mount it on a bench?
A. It can be mounted in either way. The optional Pedestal has a built in condensation trap and can be bolted to a wheel and tire or directly to the floor.
- Q. What kind of oil should I use to refill my Cyclone Shaker?
A. Use a standard petroleum 10W non-detergent rust inhibiting air tool oil, such as Conoco EP Rock Drill Oil 32, Lubriplate Rockwell 10R, or other air tool oil recommended for all air cylinders and air tools.
- Q. What are the dimensions of the Cyclone Shaker and Pedestal?
A. Shaker: 8" W X 10.5" D X 14" H (21 cm W X 27 cm D X 36 cm H) Weight: 20 lbs (9 kgs.)
Pedestal: Height: 31" (79 cm) Weight: 15 lbs (7 kgs)
- Q. What is included in the M-232RK Repair Kit?
A. (1) - M-264 Wear Ring, (1) - M-296 Check Valve Disc, (1) - M-305 Inlet Filter, (1) - M-298 Valve Body O-Ring, (2) - M-293 Transfer Body O-Ring, (1) - M-266 Head O-Ring, (1) - M-265 Piston O-Ring, (1) - M-263 Shock Bushing, (2) - M-310 Hose Clamp, (1) - M-297 Valve Disc, (1) - M-311 Air Hose.

If you would like to speak with a Sales Representative or a Technician, please call us at 248-624-7710. For technical support on our products or additional accessories, please visit our web site: www.dedoes.com.